

# Decal Installation



Start with a clean dry surface. Make sure there isn't any dirt, dust, or lint.



Tape the decal in place, check for square



Tape the decal in place, check for square with a tape measure



Once the decal is where you want it, Create a tape hinge along the top edge.



Cut between the letters where it is convenient.



Flip the decal up and peel the backing paper away from the one piece of a time. Now the transfer tape is holding the letters.



Hold the transfer sheet away from the surface with one hand. Using a squeegee, apply the graphic.



Start at the tape edge and work the squeegee back and forth while pushing the air out from beneath the graphic.



Tape the decal in place, check for square



Complete the other sections in the same manner by first removing the backing sheet.



Then apply as before until the entire graphic is down. Allow some time to pass for the adhesive to bond with the surface.



Now remove the transfer tape by pulling off slowly and at an acute angle, while making sure the vinyl stays down.



Once the entire graphic is done you can check for air bubbles and remove them with a pin in one side of the bubble and push the air out of the hole.



Allow sufficient time for the graphic to adhere before cleaning. This can be a week or more in the case of vehicles or windows.



**Ken Spencer**  
[www.NewportSignShop.com](http://www.NewportSignShop.com)  
541-867-7600

Feel free to call or email us with your questions. We are also available to install these graphics for you if you need our help.